GEM CABLE SOLUTIONS

6 Core Overall Foil and Braid Screened Cores RS232 and RS423Low Capacitance Cable 24 AWG (Belden 9931 Equiv.)

Part number: 514-005

Description:

24 AWG stranded (7x32) TC conductors, Datalene® insulation, overall Beldfoil® (100% coverage) + TC braid shield (65% coverage), drain wire, PVC jacket.



Conductor

# Conductors	AWG	Stranding	Conductor Material
6	24	7x32	TC- Tinned copper

Insulator

Insulation Material	Dia. (mm)
FPE - Foam Polyethylene	0.381

Outer Shield

Layer#	Outer shield trade name	Type	Outer shield material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil polyester tape	100
2		Braid	TC - Tinned copper	65

Outer Jacket

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.889

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +80°C
UL Temperature Rating: 80°C (UL AWM Style 2919)
Bulk Cable Weight: 52.087 Kg/Km
Min. Bend Radius/Minor Axis: 69.850 mm
Overall diameter: 6.452 mm

Electrical Characteristics

Capacitance (pF/m): 39.372
Nominal Velocity of Propagation: 78
DCR @ 20°C (Ohm/Km): 78.744
Max. Operating Voltage: 300 V RMS
Max. Recommended Current: 1.5 Amps per conductor @ 25 °C

Unit 10, The Dencora Centre, Campfield Road, St. Albans, Herts AL1 5HN, United Kingdom.
T 44 (0)1727 845750 | F 44 (0)1727 838780 | E info@gemcable.co.uk | W gemcable.co.uk

nqa. ISO 9001 Registered
UKAS QUALITY MANAGEMENT