

RADIALL® COAXIAL CONNECTORS	TECHNICAL DATA	R214.318.762	996146Z
	STRAIGHT HD CONNECTOR C-C MALE CRIMP CABLE 5.1/75 DOUBLE SCREEN PACK 20	Issue : 9618 Page Series : HDC 43 1 / 2	

PLUG HDC43/2GTIS

(PERCAGE PANNEAU)

(MOUNTING HOLE)

	MM		INCH	
	maxi	mini	maxi	mini
A	7.55	7.50	0.297	0.295

CABLES : BT2002

CHARACTERISTICS	
NOMINAL IMPEDANCE	75 Ω
FREQUENCY RANGE	0-3 GHz
TEMPERATURE RATING	-40/+100 °C
VSWR	NA + 0 x F(GHz)Maxi
RF INSERTION LOSS	NA √F(GHz) dB Maxi
VOLTAGE RATING	NA Vrms Max
DIELECTRIC WITHSTANDING VOLTAGE	1500 Vrms min
INSULATION RESISTANCE	5000 M Ωmin
HERMETIC SEAL	NA Atm.cm3/s
LEAKAGE (pressurized only)	NA Mpa
WEIGHT	10 gr

STANDARDISATION	
	-
	-
	-
	-
	-

CABLE RETENTION	
	220 N min

CENTER CONTACT RETENTION	
Axial force - mating end	22 N min
Axial force - opposite end	NA N min
Torque (Min)	NA cm.N min

RECOMMENDED TORQUES	
Mating	NA cm.N
Panel nut	NA cm.N
Clamp nut	NA cm.N

CONSTRUCTION		
CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	GOLD
OUTER CONTACT	-	-
CENTER CONTACT	BRASS	GOLD
INSULATOR	PTFE	-
FERRULE	BRASS	NICKEL
GROMMET	POLYACETAL	-
	-	-
	-	-
	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE

Initiated on **29/09/94**
 Approval by **MARTIN**

The information given here is subject to change without notice. Design changes may be in order to improve the product.

K DE A