

Product Code.: 550-002

Date: 2007-05-05

Cable Description : 3 Pairs

<u>SPECIFICATION DESCRIPTION</u>	<u>ELECTRICAL DATA</u>																		
1.) Conductor Tinned copper diameter : T0.50mm	Max.Conductor DC Resistance at 20℃（Ω/Km）95 Rated Temperature(℃)80 Working Voltage(V)150V DC,110V AC Min.Insulation DC Resistance at 20℃（MΩ*Km）50 Impedance at 1-50MHz(Ω)120+/-15																		
2.)Dielectric Thickness : 0.30mm HDCPE diameter : 1.10 mm Color: According to the custome Each pair is twisted , Unshielded.																			
3.)Mylar Spiral Coverage>115%																			
4.)Drain Wire Tinned Copper : T0.50mm																			
5.)Al-Pet Shielded Coverage>115%																			
6.)Nylon rip cord Type :210D																			
7.)Sheath PVC Thickness : 0.65mm Diameter : 5.80+/-0.15mm Color: White																			
5.)Marking According to the customer																			
6.)Packaging 1000M/Wooden Drum According to the customer																			
	Table 1 <table><tr><th rowspan="2">Pair NO:</th><th colspan="2">Color (Ring Marking)</th><th rowspan="2">Lay Length (mm)</th></tr><tr><th>A</th><th>B</th></tr><tr><td>1</td><td>WHT/BLU</td><td>BLU/WHT</td><td>62</td></tr><tr><td>2</td><td>WHT/ORG</td><td>ORG/WHT</td><td>65</td></tr><tr><td>3</td><td>WHT/GRN</td><td>GRN/WHT</td><td>68</td></tr></table>	Pair NO:	Color (Ring Marking)		Lay Length (mm)	A	B	1	WHT/BLU	BLU/WHT	62	2	WHT/ORG	ORG/WHT	65	3	WHT/GRN	GRN/WHT	68
Pair NO:	Color (Ring Marking)		Lay Length (mm)																
	A	B																	
1	WHT/BLU	BLU/WHT	62																
2	WHT/ORG	ORG/WHT	65																
3	WHT/GRN	GRN/WHT	68																