

 RADIAL COAXIAL CONNECTORS	TECHNICAL DATA	R214.088.922	
		Issue : 9606	Page 1 / 2
STRAIGHT HDC CONNECTOR C-C FEMALE CRIMP CABLE 3.6/75 DOUBLE SCREEN PACK 20		Series : HDC 43	

G96154Z

SOCKET HDC43/5FS

CABLES : BT3002		CHARACTERISTICS																																																	
<table style="width: 100%;"> <tr> <td>NOMINAL IMPEDANCE</td> <td>75 Ω</td> </tr> <tr> <td>FREQUENCY RANGE</td> <td>0-3 GHz</td> </tr> <tr> <td>TEMPERATURE RATING</td> <td>-40/+100 °C</td> </tr> <tr> <td>VSWR</td> <td>NA + - x F(BHz)Max1</td> </tr> <tr> <td>RF INSERTION LOSS</td> <td>NA $\sqrt{F}$(GHz) dB Max1</td> </tr> <tr> <td>VOLTAGE RATING</td> <td>500 Vrms Max</td> </tr> <tr> <td>DIELECTRIC WITHSTANDING VOLTAGE</td> <td>1500 Vrms min</td> </tr> <tr> <td>INSULATION RESISTANCE</td> <td>500 M Ωmin</td> </tr> <tr> <td>HERMETIC SEAL</td> <td>NA Atm.cm3/s</td> </tr> <tr> <td>LEAKAGE (pressurized only)</td> <td>NA Mpa</td> </tr> <tr> <td>WEIGHT</td> <td>10 gr</td> </tr> </table>	NOMINAL IMPEDANCE	75 Ω	FREQUENCY RANGE	0-3 GHz	TEMPERATURE RATING	-40/+100 °C	VSWR	NA + - x F(BHz)Max1	RF INSERTION LOSS	NA $\sqrt{F}$ (GHz) dB Max1	VOLTAGE RATING	500 Vrms Max	DIELECTRIC WITHSTANDING VOLTAGE	1500 Vrms min	INSULATION RESISTANCE	500 M Ω min	HERMETIC SEAL	NA Atm.cm3/s	LEAKAGE (pressurized only)	NA Mpa	WEIGHT	10 gr	<table style="width: 100%;"> <tr> <td colspan="2">STANDARDISATION</td> </tr> <tr> <td></td> <td>-</td> </tr> <tr> <td></td> <td>-</td> </tr> <tr> <td></td> <td>-</td> </tr> <tr> <td></td> <td>-</td> </tr> <tr> <td>CABLE RETENTION</td> <td>150 N min</td> </tr> <tr> <td colspan="2">CENTER CONTACT RETENTION</td> </tr> <tr> <td>Axial force - mating end</td> <td>22 N min</td> </tr> <tr> <td>Axial force - opposite end</td> <td>NA N min</td> </tr> <tr> <td>Torque (Min)</td> <td>NA cm.N min</td> </tr> <tr> <td colspan="2">RECOMMENDED TORQUES</td> </tr> <tr> <td>Mating</td> <td>NA cm.N</td> </tr> <tr> <td>Panel nut</td> <td>NA cm.N</td> </tr> <tr> <td>Clamp nut</td> <td>NA cm.N</td> </tr> </table>	STANDARDISATION			-		-		-		-	CABLE RETENTION	150 N min	CENTER CONTACT RETENTION		Axial force - mating end	22 N min	Axial force - opposite end	NA N min	Torque (Min)	NA cm.N min	RECOMMENDED TORQUES		Mating	NA cm.N	Panel nut	NA cm.N	Clamp nut	NA cm.N
NOMINAL IMPEDANCE	75 Ω																																																		
FREQUENCY RANGE	0-3 GHz																																																		
TEMPERATURE RATING	-40/+100 °C																																																		
VSWR	NA + - x F(BHz)Max1																																																		
RF INSERTION LOSS	NA $\sqrt{F}$ (GHz) dB Max1																																																		
VOLTAGE RATING	500 Vrms Max																																																		
DIELECTRIC WITHSTANDING VOLTAGE	1500 Vrms min																																																		
INSULATION RESISTANCE	500 M Ω min																																																		
HERMETIC SEAL	NA Atm.cm3/s																																																		
LEAKAGE (pressurized only)	NA Mpa																																																		
WEIGHT	10 gr																																																		
STANDARDISATION																																																			
	-																																																		
	-																																																		
	-																																																		
	-																																																		
CABLE RETENTION	150 N min																																																		
CENTER CONTACT RETENTION																																																			
Axial force - mating end	22 N min																																																		
Axial force - opposite end	NA N min																																																		
Torque (Min)	NA cm.N min																																																		
RECOMMENDED TORQUES																																																			
Mating	NA cm.N																																																		
Panel nut	NA cm.N																																																		
Clamp nut	NA cm.N																																																		

CONNECTOR PARTS	MATERIALS	FINISH
BODY	BRASS	NICKEL
OUTER CONTACT	BRONZE	GOLD
CENTER CONTACT	BERYLLIUM COPPER	GOLD
INSULATOR	PTFE	-
COUPLING SLEEVE	BRASS	NICKEL
FERRULE	BRASS	NICKEL
-	-	-
-	-	-
-	-	-

TABLE	REVISION No	DESCRIPTION	BY	DATE
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

Initiated on 09/02/96	The information given here is subject to change without notice. Design changes may be in order to improve the product	
Approval by MARTIN		

GERALD U