

SPEC NO.: 550-006


Product Code.: RD8567

Date: 2007-05-05

Cable Description : 25 Pairs

<u>SPECIFICATION DESCRIPTION</u>	<u>ELECTRICAL DATA</u>
1.) Conductor Tinned copper diameter : T0.50mm 2.) Dielectric Thickness : 0.30mm HDCPE diameter : 1.10 mm Color: According to the custome Each pair is twisted , Unshielded. 3.) Mylar Spiral Coverage>115% 4.) Drain Wire Tinned Copper : T0.50mm 5.) Al-Pet Shielded Coverage>115% 6.) Nylon rip cord Type :210D 7.) Sheath PVC Thickness : 0.90mm Diameter : 12.96+/-0.15mm Color: White 5.) Marking According to the customer 6.) Packaging 1000M/Wooden Drum According to the customer	Max.Conductor DC Resistance at 20°C (Ω/Km) 95 Rated Temperature(°C) 80 Working Voltage(V) 150V DC,110V AC Min.Insulation DC Resistance at 20°C (MΩ*Km) 50 Impedance at 1-50MHz(Ω) 120+/-15

Design:



OTHER

We operate according to the following standards
RoHS GUIDELINE

Control Item	Testing Equipment	Testing Method	Standard
Cadmium content (Cd)	ICP-AES	EN1122	<0.01%
Lead content (Pb)	ICP-AES	EPA3050B	<0.1%
Mercury content (Hg)	ICP-AES	EPA3052	<0.1%
Chromium (VI) content	ICP-AES	EPA3060(UN-VIS)	<0.1%
Polybrominated Biphenyls(PBB)		GC/MS	Forbidden
Polybrominated Diphenyl Ether (PBDE)		GC/MC	Forbidden