


GBC195 LSZH Coax Cable

LMR195FR® Direct Equivalent Cable

201-104



- Jumper Assemblies in Wireless Communications Systems
- Short Antenna Feeder Runs
- Any application (e.g. WLL, GPS, LMR, WLAN, WISP, WiMax, SCADA, Mobile Antennas) requiring an easily routed low loss RF cable

Construction Specifications		
1 Inner Conductor	Bare Copper Clad Aluminium	0.94mm
2 Dielectric	Physical Foam Polyethylene	2.79mm
3 Outer Conductor	Bonded Aluminium Foil	2.95mm
4 Overall Braid	Tinned Copper	3.53mm
5 Jacket	Low Smoke Halogen Free	4.95mm





Electrical Specifications	
1 Impedance	50 Ω
2 Capacitance	83.3 pF/M (25.4 pF/ft)
3 Velocity of Propagation	76%
4 Voltage Withstand	1000 VDC
5 Max Operating Frequency	18.0 GHz

Environmental Specifications	
1 Bending Radius Static	12.7mm (0.5")
2 Bending Radius Repeated	50.8/mm (2.0")
3 Weight	21Kg/Km



PE
Version
Also
Available

Frequency (MHz)	150	220	450	900	1500	1800	2000	2500	3000	5800
Attenuation dB/100m	14.6	17.7	25.5	36.5	47.7	52.5	55.4	62.4	68.8	98.1
Avg. Power kW	0.39	0.32	0.22	0.16	0.12	0.11	0.10	0.09	0.08	0.06

Connectors*				
				
N Type Crimp Plug	TNC Crimp Plug	SMA Crimp Plug	N Type Clamp Plug	N Type Clamp Socket

*Only A Selection of Connectors Shown, More Available From Stock

**We Manufacture Your
Cable Assemblies
To Your Spec**



Although GEM Cable Solutions makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.