

HUBER+SUHNER[®] DATA SHEET

Coaxial Cable Connector: 11_QLA-01-3-2/122_N

Rev.: A



Description

Straight cable plug for flexible cable

Interface standards

NIM-CAMAC-Standard CD/N549



Technical Data

Electrical Data

Impedance	other Ω
Interface frequency max.	1.4 GHz

Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0051 kg

Environmental Data

Operating Temperature	-55 °C to 150 °C
-----------------------	------------------

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Nickel Plating
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Catalogue drawing	DOU-00006540
Assembly instruction	DOC-0000180108

Ordering Information

Single package	11_QLA-01-3-2/122_NE
----------------	----------------------

Additional Information

Suitable cables	RG_223_U, RG_142_B/U
-----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: DOC-0000183055 G.00

Issued:

Uncontrolled Copy

Page 1/1



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com