

A

B

C

D

REV	ECO	DWN	DATE
A	20099549	JRA	13-SEP-01
-	-	-	-

FIN

TOP VIEW

POSITION FIN IN-LINE WITH
TROUGH ENTRANCE AND EXIT.
FIN EDGES MUST MAINTAIN
TANGENCY TO CABLE ROUTING

CABLE REF

NOTES:

1. FIN SHOULD BE STORED AT ROOM TEMPERATURE FOR OPTIMUM PERFORMANCE.
 2. SHELF LIFE : 12 MONTHS.
 3. IDEAL APPLICATION TEMPERATURE RANGE IS 70°F TO 100°F. MINIMUM APPLICATION TEMPERATURE IS 60°F.
 4. TO OBTAIN OPTIMUM ADHESION, THE BONDING SURFACE MUST BE CLEAN AND DRY. TYPICAL SURFACE CLEANING SOLVENTS ARE ISOPROPYL ALCOHOL/WATER MIXTURE (RUBBING ALCOHOL).
- NOTE: BE SURE TO FOLLOW SOLVENT MANUFACTURES PRECAUTIONS AND DIRECTIONS FOR USE WHEN USING SOLVENTS.
5. PREDETERMINE LOCATION (SEE TOP VIEW) OF FIN IN TROUGH BEFORE REMOVING ADHESIVE LINER. ONCE FIN IS BONDED IN PLACE, IT CANNOT BE REMOVED.
 6. REMOVE ADHESIVE LINER AND POSITION FIN IN TROUGH. APPLY FIRM PRESSURE OVER ENTIRE FIN BASE TO ENSURE A FULL BOND.



INFORMATION ON THIS DOCUMENT IS
PROPRIETARY TO ADC AND SHALL
NOT BE USED, COPIED, REPRODUCED
OR DISCLOSED IN WHOLE OR IN PART
WITHOUT WRITTEN CONSENT OF ADC.

ALL DIMS AND TOLERANCES .XX:±.XX
ARE INCHES UNLESS .XXX:±.XXX
OTHERWISE SPECIFIED ANGULAR:±N/A



DO NOT
SCALE DRAWING

ENGR: M. FERRIS
DWN: J. ANDERSON

TITLE INSERT, FIN,
W/TAPE, FGS
INSTALLATION DWG

DRAWING NUMBER
1195947

A
REV

SHT. 1 OF 1

A

B

C

D